

Without measurement there is no control®

MiniCapt® Compressed Gas Kit

Microbial Monitoring Accessory



Precise compressed gas monitoring for use with the MiniCapt® Mobile

The MiniCapt® Compressed Gas kit allows the MiniCapt Mobile Microbial Sampler to perform microbiological monitoring of compressed gases. The compressed gas kit is designed to work with either the 25 LPM, 50 LPM, or 100 LPM MiniCapt Mobile.

This compressed gas kit uses a special diffusion chamber mounted directly to the MiniCapt inlet, the other end of which is connected directly to the high pressure gas distribution line. For safety reasons and to regulate the flow rate of the gas into the diffusion chamber, a pressure regulator is installed in the sampling line between the high pressure gas source and the inlet to the kit. A solenoid valve is connected downstream of regulator and allows the MiniCapt to synchronize the flow of the gas with the start of a sample.

The flow of the gas to be sampled is controlled using the principle of the critical orifice. Under operating pressures, the critical orifice regulates the flow rate into the diffusion chamber and the exhaust.

BENEFITS

- Small size for easy access to sampling points
- Economical monitoring of pressurized gases with atmospheric pressure
- Accessory to an already validated instrument
- Does not need additional qualification
- Relatively low weight compared to competitive instruments
- HEPA air filter for overpressure air and inversion from low pressure/flow prevents contamination

FEATURES

- Measures gases with pressures of 0.5 to 10 bar (7.2 - 145 psi) with the range model-dependent
- Can be used with clean dry air (CDA), argon, nitrogen, carbon dioxide and other non-toxic inert gases
- No external flow meters needed
- Three different versions: 25, 50 and 100 LPM flow rates
- No moving parts to wear
- Autoclavable stainless steel construction (removable solenoid valve)
- Ease of cleaning with isopropyl alcohol 70/30, sodium hypochlorite 1%, and hydrogen peroxide (up to 6%)

APPLICATIONS

- MiniCapt Mobile (25, 50, 100 LPM)

MiniCapt® Compressed Gas Kit Microbial Monitoring Accessory

PARAMETER	SPECIFICATION
Pressure	0.5 – 10 bar (7.2 – 145 psi) for 25 LPM flow rate 1.0 – 10 bar (14.5 – 145 psi) for 50 LPM flow rate 1.5 – 10 bar (21.7 – 145 psi) for 100 LPM flow rate
Flow rate	Options for 25 LPM, 50 LPM, or 100 LPM with MiniCapt Mobile
Material	316L stainless steel expansion chamber, regulator, adaptor and solenoid valve
Sample gas	Dry, inert, non-toxic, non-flammable gases (CDA, nitrogen, argon, carbon dioxide) Note: For carbon dioxide sampling, contact Particle Measuring Systems.
Inlet fitting	G1/8 BSPP threaded 0.236 in (6 mm) outer diameter tubing
Exhaust fitting	316L stainless steel 0.875 in (22 mm) connection to filter
ISO class	ISO Class 5, 6, 7 and 8
Dimensions (h, w, d)	8.5 x 6 x 4 in (21.6 x 15.2 x 10.2 cm)
Weight	4.1 lb (1.86 kg)
Compatible instruments	MiniCapt Mobile (25, 50, 100 LPM)

System components included: diffusion chamber, dual connection impactor, absolute filter, solenoid valve and cable, pressure regulator, and pressure tubing

Not included: MiniCapt Mobile

NEED MORE INFORMATION? Scan the QR code to connect with our team for guidance



HEADQUARTERS

7477 E. Dry Creek Parkway,
Niwot, CO, 80503 USA
T: +1 303 443 7100

Instrument Service & Support
T: +1 303-443-7100 ext.447

Service and Calibration
E: workorders@pmeasuring.com

Technical Support
E: techsupport@pmeasuring.com

Software or System Support
E: ssupport@pmeasuring.com

Customer Service and Order Processing
E: customerorders@pmeasuring.com

GLOBAL OFFICES

AUSTRIA
T: +43 171 728 285
E: pmsaustria@pmeasuring.com

BELGIUM/BENELUX
T: +32 10 23 71 56
E: pmsbelgium@pmeasuring.com

BRAZIL
T: +55 11 5188 8227
E: pmsbrazil@pmeasuring.com

CHINA
T: +86 400 081 8020
E: pmschina@pmeasuring.com

FRANCE
T: +33 682 991 798
E: pmsfrance@pmeasuring.com

GERMANY
T: +49 351 8896 3850
E: pmsgermany@pmeasuring.com

IRELAND
T: +353 1 295 7373
E: Info.ie@pmeasuring.com

ITALY
T: +39 06 9053 0130
E: pmsrli@pmeasuring.com

JAPAN
T: +81 44 589 3498
E: pmsjapan@pmeasuring.com

KOREA
T: +82 31 286 5790
E: pmskorea@pmeasuring.com

NORDIC
T: +45 7070 2855
E: pmsnordic@pmeasuring.com

PUERTO RICO
T: +1 786 564 3356
E: pmspuertorico@pmeasuring.com

SINGAPORE
T: +65 6496 0342
E: pmssingapore@pmeasuring.com

SWITZERLAND
T: +41 71 987 01 01
E: pmsswitzerland@pmeasuring.com

TAIWAN
T: 886-3-5525300
E: pmstaiwan@pmeasuring.com

UNITED KINGDOM
T: +44 (0)1733 454 207
E: Info.uk@pmeasuring.com



FacilityPro® and Lasair® are registered trademarks of Particle Measuring Systems, Inc. All other trademarks are the property of their respective owners. Particle Measuring Systems, Inc. reserves the right to change specifications without notice. © 2026 Particle Measuring Systems, Inc. All rights reserved. 06162026