

Without measurement there is no control®

# MiniCapt® Mobile

## Mobile Microbial Air Sampler



### Innovative, light mobile air sampler applying modern data management capabilities

The MiniCapt® Mobile Microbial Air Sampler allows the user to perform viable air sampling in cleanroom environments for classification and monitoring purposes.

Available in three flowrate models, the MiniCapt Mobile sampler is designed for any cleanroom, including critical environments such as ISO Class 5 and GMP Grade A.

This top tier instrument incorporates modern data management capabilities and an easy, interactive touchscreen interface. Connected with the latest DataAnalyst software, users can manage sampling data and microbial counts in a complete paperless solution. Data is secure with uneditable file exports. Connecting to several accessories is easy, and cleanroom contamination is avoided with built-in HEPA filtration.

The impactor head design has 20 precision-cut radial slits and an adjustable height and plate diameter mechanism that allow the MiniCapt Mobile sampler to be used with almost all manufactured agar plates, including glass Petri plates. The radial slits also ensure laminar flow, making false positive identification easier.

### BENEFITS

#### Flexibility

- Multiple applications (isolator sampling, compressed gases, remote and handheld usages)
- Operates with BioCapt® Single-Use units
- Adjustable height and diameter mechanism for versatile Petri dish compatibility

#### Precision

- Meets ISO 14698-1
- Radial slit design for optimal microorganism recovery during sampling
- Immediate and easy detection of false-positive results
- Feller correction only above 57 CFU, max 3% overlap deviations at 200 CFU

#### Security

- HEPA-filtered exhaust ensures no environmental contamination of critical control points
- Autoclavable 316L stainless steel impactor head

### FEATURES

- Modern data and sample configuration management
- Multiple levels of security
- Management of microbial counts and data analysis with DataAnalyst software (Version 3.0+)
- Uneditable data records, reports and file exports
- Error reduction with intuitive user interface and pre-configured sampling recipes

### APPLICATIONS

- Microbial air sampling in cleanrooms and associated controlled environments
- USP 797 environmental viable-airborne particle testing
- Microbial monitoring of medical device manufacturing environments

# MiniCapt® Mobile Mobile Microbial Air Sampler

MINICAPT	25M	50M	100M
Sampling flow rate	25 Liters/minute	50 Liters/minute	100 Liters/minute
Battery (Lithium ion) <sup>1</sup>	12 hours	7 hours	6 hours
Power supply	Input: 100 – 240 VAC, 50/60 Hz, 1.5 A		
Memory	3,000 Samples; 400 Areas/Locations; 50 Recipes		
Sampling modes	Volume or Time; Interval sampling		
Sampling interval	Time: 1 – 400 min	1 – 200 min	1 – 100 min
	Volume: 1 – 9999 L	1 – 9999 L	1 – 9999 L
Communication	Modbus TCP; USB for data download; USB for printer connection		
Display	4.3" VGA (480 x 272) LCD with touchscreen		
Display Languages	English, French, German, Italian, Japanese, Korean, Spanish, Chinese (traditional or simplified), Russian, Portuguese		
Dimensions (h, w, d)	10.2 x 5.7 x 5.9 in (26.0 x 14.5 x 15.0 cm)		
Weight	4.6 lb (2.1 kg)		
Operating environment	Temperature: 32 – 104 °F (0 – 40 °C); Humidity: 10 – 90% RH		
Calibration interval	Recommended every 12 months		

<sup>1</sup> Battery life based on sampling 10 minutes, pausing 5 minutes, and repeating..

BIOCAPT IMPACTOR HEAD	
Materials	AISI 316L Stainless Steel
Number of Inlets	20 (Precision-cut slits)
ACCESSORIES	
<ul style="list-style-type: none"> <li>Compressed Gas Sampling Kit</li> <li>Isolator Monitoring Kit</li> <li>Base Mounting Kit</li> <li>Remote Sampling Kit for BioCapt Adjustable Height</li> </ul>	<ul style="list-style-type: none"> <li>Remote Sampling kit for BioCapt Single-Use (25 and 50 LPM only)</li> <li>Remote ISP Sampling Kit</li> <li>Petri Dish Barcode Reader</li> <li>External Printer Kit</li> </ul>

## Accessories



**NEED MORE INFORMATION?** Scan the QR code to connect with our team for guidance



**HEADQUARTERS**  
7477 E. Dry Creek Parkway,  
Niwot, CO, 80503 USA  
T: +1 303 443 7100  
**Instrument Service & Support**  
T: +1 303-443-7100 ext.447  
**Service and Calibration**  
E: workorders@pmeasuring.com  
**Technical Support**  
E: techsupport@pmeasuring.com  
**Software or System Support**  
E: ssupport@pmeasuring.com  
**Customer Service and Order Processing**  
E: customerorders@pmeasuring.com

**GLOBAL OFFICES**  
**AUSTRIA**  
T: +43 171 728 285  
E: pmsaustria@pmeasuring.com  
**BELGIUM/BENELUX**  
T: +32 10 23 71 56  
E: pmsbelgium@pmeasuring.com  
**BRAZIL**  
T: +55 11 5188 8227  
E: pmsbrazil@pmeasuring.com  
**CHINA**  
T: +86 400 081 8020  
E: pmschina@pmeasuring.com

**FRANCE**  
T: +33 682 991 798  
E: pmsfrance@pmeasuring.com  
**GERMANY**  
T: +49 351 8896 3850  
E: pmsgermany@pmeasuring.com  
**IRELAND**  
T: +353 1 295 7373  
E: Info.ie@pmeasuring.com  
**ITALY**  
T: +39 06 9053 0130  
E: pmsrsl@pmeasuring.com

**JAPAN**  
T: +81 44 589 3498  
E: pmsjapan@pmeasuring.com  
**KOREA**  
T: +82 31 286 5790  
E: pmskorea@pmeasuring.com  
**NORDIC**  
T: +45 7070 2855  
E: pmsnordic@pmeasuring.com  
**PUERTO RICO**  
T: +1 786 564 3356  
E: pmspuertorico@pmeasuring.com

**SINGAPORE**  
T: +65 6496 0342  
E: pmssingapore@pmeasuring.com  
**SWITZERLAND**  
T: +41 71 987 01 01  
E: pmsswitzerland@pmeasuring.com  
**TAIWAN**  
T: 886-3-5525300  
E: pmstaiwan@pmeasuring.com  
**UNITED KINGDOM**  
T: +44 (0)1733 454 207  
E: Info.uk@pmeasuring.com



FacilityPro® and Lasair® are registered trademarks of Particle Measuring Systems, Inc. All other trademarks are the property of their respective owners. Particle Measuring Systems, Inc. reserves the right to change specifications without notice. © 2026 Particle Measuring Systems, Inc. All rights reserved. 06162026